















Oil Immersed Brakes

100 FARIT

Heavy Duty Front Axle

INDO FRRM

Reverse PTO







Years of Trust

Reverse PTO

DC Valve

Dual Clutch

INDO FARM 3055 NV C-MESH (2WD/4WD)

Technical Specifications

		2WD	4WD	
H.P. Category		55		
Туре		Diesel, Four Stroke Direct Injection		
No. of Cylinders		Three		
Bore/Stroke		105/110 mm		
Rated Speed		2200 RPM		
Air Cleaner		Dry Type		
Fuel Pump		Inline, Make : Bosch India		
Cooling System		Water cooled		
Clutch System		Dual Clutch		
Hyd. Pump		Gear Type		
Lifting Capacity		1800 kg at Lower Link Ends		
Electrical		12 Volts-75 Ah-Battery Self Starter Motor & Alternator		
Tyre	Front	7.50 x 16	8.00 x 18	
	Rear	14.9 x 28	14.9 x 28	
Wheel Track		1355-1940 mm	1310-1940 mm	
Measurement	-	3700 mm	3760 mm	
	Width	1850 mm		
	Height upto steering	1680 mm		
	Min. Ground Clearance	420 mm	370 mm	
Min. Turning ra	adius	3.5 m	4.0 m	
Weight		2260 kg	2370 kg	
PT.O. 1. No. of Splines 2. PTO Speed		6 540 RPM		
Driver's Seat		Adjustable		
Transmission No. of Gear Speeds		8 Forward 2 Reverse		
Steering		Power Steering		
Steering wheel dia		380 mm		
Brake Type		Oil Immersed Brake		
Actuation		Mechanical, independent right/left or combined		
Parking		Through hand lever, by locking brake pedals		

Hydraulic (ADDC) : Two lever, automatic Draft and Position control with mix control.

- 1. Position Control : To pre-select and automatically maintain certain position or depth of the implement attached to three-point-linkage.
- 2. Draft Control : To automatically raise and lower an attached implement as the draft or resistance of the implement increases or decreases.
- 3. Mix Control : To automatically maintain shallow depths in loose soils where draft control is inefficient.

Gear Speed (14.9 x 28 Rear Tyre)							
		Road Speed (km/h)					
Direction	Gear	Low		High			
		Normal	16+4	Normal	16+4		
Forward	1	2.22	0.56	8.91	2.26		
	2	3.12	0.80	12.68	3.22		
	3	5.00	1.27	20.04	5.09		
	4	8.21	2.09	32.93	8.36		
Reverse	1	2.95	0.75	11.82	3.00		

Suitable Implements		
	11 Tine Tiller	
	3 Bottom M.B. Plough	
	14 Disk Harrow	
	5 Ton Trailor	
	Rotavator 42 blades	

Accessories with Every Tractor

- Trailor Hook
- Draw bar
- Fender Guard
- Heavy Bumper
- Tool Kit
- Operator Manual

All the above specifications are subject to change without notice. For detailed information contact your nearest dealer.

Authorised Dealer

SPECIAL FEATURES



levers for easy gear shifting & more leg space.



Straight Rear Axle, Less maintenance and repair






Heavy Duty Front Axle (4WD)/ Power Steering



Heavy 1800 kgs Lift, suitable for heavy implements and tipping trailers with higher loads



Oil immersed Brakes for better braking due to larger braking area & longer life due to oil cooling.



Use to lift the trolley without

Dry Air Cleaner



Export Promotion Industrial Park, Phase-II, Baddi - 173205 Distt. Solan, H.P. Tel. : +91-1795-274242 to 247, Email: mail@indofarm.in, Website: www.indofarm.in

