





















INDO FARM





ATTAIN AND





Power Steering

Heavy 1800 Kgs Lift 0

Oil Immersed Brakes Heavy Duty Front Axle

Reverse PTO

e

Dry Air Cleaner

Front Weight

INDO FARM 3065 DI TS-VI C-MESH

Technical Specifications

		2WD		
H.P. Category		65		
Туре		Diesel, Four Stroke Direct Injection		
No. of Cylinders		Four		
Bore/Stroke		105/118 mm		
Rated Speed		2200 RPM		
Air Cleaner		Dry Туре		
Fuel Pump		Inline, Make : Bosch India		
Cooling System		Water cooled		
Clutch System		Dual Clutch		
Hyd. Pump		Gear Type		
Lifting Capacity		1800 kg at Lower Link Ends		
Electrical		12 Volts-88 Ah-Battery Self Starter Motor & Alternator		
Tyre Front Rear		7.50x16 16.9x28		
Wheel Track		1480-1991 mm		
Dimensions	Length	3880 mm		
&	Width	1940 mm		
Weight	Height upto steering	1710 mm		
	Min. Ground Clearance	420 mm		
	Min. Turning Radius	4.0 m		
	Weight	2370 Kg		
PT.O. 1. No. of Splines 2. PTO Speed		6 540 RPM		
Driver's Seat		Adjustable		
Transmission No. of Gear Speeds		16 Forward 4 Reverse		
Steering		Hydrostatic Power Steering		
Brake Type		Oil Immersed Brake		
Brake Actuation		Mechanical, independent right/left or combined		
Parking Brake Actuation		Through hand lever, by locking brake pedals		

	d (km/h)						
Direction	Gear	Low		High			
Direction		Normal	16+4	Normal	16+4		
Forward	1	2.82	0.72	11.30	2.87		
	2	4.01	1.02	16.09	4.09		
	3	6.34	1.61	25.41	6.45		
	4	8.60	2.18	34.48	8.75		
Reverse	1	3.74	0.95	15.00	3.81		

Gear Speed (16.9 x 28 Bear Tyre)

Suitable Implements				
13 Tine Tiller				
3 Bottom M.B. Plough				
16 Disk Harrow				
7 Ton Trailor				
Rotavator 48 blades				

Accessories with Every Tractor

- Trailor Hook
- Draw bar
- Fender Guard
- Heavy Bumper
- Tool Kit
- Operator Manual

Accessories/Farm implements shown with tractors are not part of the standard model.

All the above specifications are subject to change without notice. For detailed information contact your nearest dealer.

Authorised Dealer

SPECIAL FEATURES



Constant Mesh Gear Box with Side shift gear levers for easy gear shifting & more leg space.



Straight Rear Axle, Less maintenance and repair



Power Steering



Oil immersed Brakes for better braking due to larger braking area & longer life due to oil cooling.



Heavy 1800 kgs Lift, suitable for heavy implements and tipping trailers with higher loads



Aerodynamic Design- Easy approach for daily checkup like coolant level, air cleaner etc.



Use to lift the trolley without

lifting of hydraulic lift.

Dry Air Cleaner



Export Promotion Industrial Park, Phase-II, Baddi - 173205 Distt. Solan, H.P. Tel. : +91-1795-274242 to 247, Email: mail@indofarm.in, Website: www.indofarm.in

Hydraulic (ADDC) : Two lever, automatic Draft and Position control with mix control.

- 1. Position Control : To pre-select and automatically maintain certain position or depth of the implement attached to three-point-linkage.
- 2. Draft Control : To automatically raise and lower an attached implement as the draft or resistance of the implement increases or decreases.
- 3. Mix Control : To automatically maintain shallow depths in loose soils where draft control is inefficient.