



INDO FARM 3075 DI C-MESH TS-IV













INDO FRAM



INDO FARM









Heavy 2400 Kgs Lift

Oil Immersed Brakes Heavy Duty Front Axle

Reverse PTO

Dry Air Cleaner

Front Weight

Years of Trust

INDO FARM 3075 DI C-MESH TS-IV

Technical Specifications

H.P. Category		75			
Туре		Diesel, Four Stroke Direct Injection			
No. of Cylinders		Four			
Bore/Stroke		105/118 mm			
Rated Speed		2200 RPM			
Air Cleaner		Dry Type			
Fuel Pump		Inline, Make : Motorpal			
Cooling System		Water cooled			
Clutch System		Dual Clutch			
Hyd. Pump		Gear Type			
Lifting Capacity		2400 kg at Lower Link Ends			
Electrical		12 Volts-88 Ah-Battery			
		Self Starter Motor & Alternator			
Tyre Front		7.50 x 16			
Rear		16.9 x 30 1586-1480 mm			
Wheel Track (Front-Rear) Dimensions Length					
Dimensions &	Width	3890 mm 1980 mm			
Weight Height upto		1740 mm			
weigin	steering	1740 11111			
	Min. Ground Clearance	420 mm			
Min. Turning Radius Weight		4.5 m			
		2460 kgs			
PT.O. 1. No. of Splines 2. PTO Speed		6 540 RPM			
Driver's Seat		Adjustable			
Transmission No. of Gear Speeds		8 Forward 2 Reverse			
Steering		Hydrostatic Power Steering			
Brake Type		Oil Immersed brake			
Brake Actua	tion	Mechanical, independent right/left or combined			
Parking Brake Actuation		Through hand lever, by locking brake pedals			
Ju					

Hydraulic (ADDC)	:	Two	lever,	automatic	Draft	and	Position	control	with	mix
control.										

- 1. Position Control : To pre-select and automatically maintain certain position or depth of the implement attached to three-point-linkage.
- 2. Draft Control : To automatically raise and lower an attached implement as the draft or resistance of the implement increases or decreases.
- 3. Mix Control : To automatically maintain shallow depths in loose soils where draft control is inefficient.

Gear Speed (16.9 x 30 Rear Tyre)							
		Road Speed (km/h)					
Dimention	Gear	Lo	W	High			
Direction	uoui	Normal	16+4	Normal	16+4		
Forward	1	2.92	??	11.72	??		
	2	4.16		16.69			
	3	6.58		26.36			
	4	8.92		35.76			
Reverse	1	3.88		15.55			

Suitable Implements
17/15 Tine Tiller
4 Bottom M.B. Plough
20 Disk Harrow
7.5 Ton Trailor
Rotavator 54 blades

Accessories with Every Tractor

- Trailor Hook
- Draw bar
- Fender Guard
- Front Weight
- Tool Kit
- Operator Manual
- Canopy on Demand

Accessories/Farm implements shown with tractors are not part of the standard model.

All the above specifications are subject to change without notice. For detailed information contact your nearest dealer.

Authorised Dealer

SPECIAL FEATURES



levers for easy gear shifting & more leg space.



Straight Rear Axle, Less maintenance and repair





Heavy Duty Front Axle



implements and tipping trailers with higher loads

Use to lift the trolley without lifting of hydraulic lift.



checkup like coolant level, air cleaner etc.

Oil immersed Brakes for better braking

due to larger braking area & longer life due to oil cooling.

Dry Air Cleaner



Export Promotion Industrial Park, Phase-II, Baddi - 173205 Distt. Solan, H.P. Tel. : +91-1795-274242 to 247, Email: mail@indofarm.in, Website: www.indofarm.in