











INDO FARM 3035 DI

Technical Specifications

	3035 DI		
H.P. Range	38		
Туре	Diesel, Four Stroke Direct Injection		
No. of Cylinders	Three		
Bore/Stroke	105/110 mm		
Compression Ratio	19:1		
Rated Speed	2100 RPM		
Max. Torque Speed	1200-1400 RPM		
Air Cleaner	Dry Type		
Fuel Pump	Inline, Make : Bosch India		
Cooling System	Water cooled		
Clutch System	l Single ii) Main Clutch disc Cerametallic		
Hyd. Pump	Gear Type		
Lifting Capacity	1400 kg at Lower Link Ends		
Electrical System	12 Volts-75 Ah-Battery Self Starter Motor & Alternator		
Tyre Front Rear	6.00 x 16 12.4 x 28		
Wheel Track	1355-1895		
Measurement Length Width Height upto steering	3600 mm 1670 mm 1615 mm		
Min. Ground Clearance	385 mm		
Weight	1980 kg		
P.T.O. 1. No. of Splines 2. PTO Speed	6 1000 RPM		
Driver's Seat	Adjustable		
Transmission No. of Gear Speeds	8 Forward 2 Reverse		
Steering	i) Mechanical - Recirculating ball type ii) Power Steering (Optional)		
Steering wheel dia	430 mm		
Min. Turning radius	3.2 m		
Brake Type	i) Dry: Double disc type (190 mm dia) with parking brake lever ii) Wet: Oil immersed multiple discs (Optional)		

Hydraulic (ADDC): Two lever, automatic Draft and Position control with mix control.

- Position Control: To pre-select and automatically maintain certain position or depth of the implement attached to three-point-linkage.
- 2. Draft Control: To automatically raise and lower an attached implement as the draft or resistance of the implement increases or decreases.
- Mix Control: To automatically maintain shallow depths in loose soils where draft control is inefficient.

Gear Speed (12.4 x 28 Rear Tyre)				
Direction	Gear	Road Speed (km/h)		
		Low	High	
Forward	1	2.10	8.29	
	2	3.26	12.84	
	3	4.87	19.16	
	4	7.48	29.45	
Reverse	1	2.63	10.36	

Suitable Implements		
9 Tine Tiller		
2 Bottom M.B. Plough		
12 Disk Harrow		
4 Ton Trailor		
Rotavator 36 blades		


Accessories with Every Tractor

- Trailor Hook
- Draw bar
- Fender Guard
- Heavy Bumper
- Tool Kit
- Operator Manual

All the above specifications are subject to change without notice. For detailed information contact your nearest dealer.

Authorised Dealer

SPECIAL FEATURES



8+2 Speed Gear Box. Speeds available for all applications.



Brakes on Intermediate shafts resultin in no water ingress during puddling.



Straight Rear Axle for easy maintenance and minimum wear & tear.



Recirculating Ball type Steering prevents transmission of shocks to the steering wheel



Epicyclic Reduction for High/Low Speeds-reduces noise & increases life.



Oil immersed Brakes for better braking due to larger braking area & longer life due to oil cooling.



Aerodynamic Design- Easy approach for daily checkup like coolant level, air cleaner etc.



Dry Air Cleaner





Export Promotion Industrial Park, Phase-II, Baddi-173 205, Distt. Solan, H.P. Tel.: (+91)-1795-274241 (8 Lines); Fax: (+91)-1795-274308-309 Email: mail@indofarm.in; Website: www.indofarm.in