



India 1st Most  
**POWER+MILEAGE**  
Tractor Range

**INDO FARM**  
**3055 DI**  
**C-MESH**

**4x4**



Power Steering



Heavy 1800 Kgs Lift



Oil Immersed Brakes



Heavy Duty Front Axle



Reverse PTO



DC Valve



Dual Clutch



Dry Air Cleaner



Front Weight

# INDO FARM 3055 DI C-MESH 4x4

## Technical Specifications

	2WD	4WD	
H.P. Category	60		
Type	Diesel, Four Stroke Direct Injection		
No. of Cylinders	Four		
Bore/Stroke	105/118 mm		
Rated Speed	2200 RPM		
Air Cleaner	Dry Type		
Fuel Pump	Inline, Make : Bosch India		
Cooling System	Water cooled		
Clutch System	Dual Clutch		
Hyd. Pump	Gear Type		
Lifting Capacity	1800 kg at Lower Link Ends		
Electrical	12 Volts-88 Ah-Battery Self Starter Motor & Alternator		
Tyre	Front	7.50x16	
	Rear	16.9x28	
Tyre	Front	9.50 x 24	
	Rear	16.9 x 28	
Wheel Track	1426-1940 mm		
Dimensions & Weight	Length	3810 mm	
	Width	1814 mm	
Weight	Height upto steering	1710 mm	
	Min. Ground Clearance	420 mm	380 mm
	Min. Turning Radius	4.0 m	5.0 m
	Weight	2350 Kg	2750 kg
P.T.O.			
1. No. of Splines	6		
2. PTO Speed	540 RPM		
Driver's Seat	Adjustable		
Transmission			
No. of Gear Speeds	8 Forward 2 Reverse		
Steering	Hydrostatic Power Steering		
Brake Type	Oil Immersed Brake		
Brake Actuation	Mechanical, independent right/left or combined		
Parking Brake Actuation	Through hand lever, by locking brake pedals		

**Hydraulic (ADDIC) :** Two lever, automatic Draft and Position control with mix control.

1. Position Control : To pre-select and automatically maintain certain position or depth of the implement attached to three-point-linkage.
2. Draft Control : To automatically raise and lower an attached implement as the draft or resistance of the implement increases or decreases.
3. Mix Control : To automatically maintain shallow depths in loose soils where draft control is inefficient.

Gear Speed (14.9 x 28/16.9 x 28 Rear Tyre)					
Direction	Gear	Road Speed (km/h)			
		Low		High	
		14.9 x 28	16.9 x 28	14.9 x 28	16.9 x 28
Forward	1	2.69	2.82	10.79	11.30
	2	3.83	4.01	15.37	16.09
	3	6.06	6.34	24.27	25.41
Reverse	4	8.21	8.60	32.94	34.48
	1	3.57	3.74	14.32	15.00

### Suitable Implements

13 Tine Tiller
3 Bottom M.B. Plough
16 Disk Harrow
7 Ton Tractor
Rotavator 48 blades

### Accessories with Every Tractor

- Tractor Hook
- Draw bar
- Fender Guard
- Heavy Bumper
- Tool Kit
- Operator Manual

Accessories/Farm implements shown with tractors are not part of the standard model.

All the above specifications are subject to change without notice.  
For detailed information contact your nearest dealer.

**Authorised Dealer**

## SPECIAL FEATURES



Constant Mesh Gear Box with Side shift gear levers for easy gear shifting & more leg space.



Straight Rear Axle, Less maintenance and repair



Heavy Duty Front Axle (2WD)/ Power Steering



Heavy Duty Front Axle (4WD)/ Power Steering



Heavy 1800 kgs Lift, suitable for heavy implements and tipping trailers with higher loads



Use to lift the trolley without lifting of hydraulic lift.



Oil immersed Brakes for better braking due to larger braking area & longer life due to oil cooling.



Dry Air Cleaner

**INDO FARM EQUIPMENT LIMITED**

AN ISO 9001 : 2015 CERTIFIED COMPANY

Export Promotion Industrial Park, Phase-II, Baddi - 173205 Distt. Solan, H.P.  
Tel. : +91-1795-274242 to 247, Email: mail@indofarm.in, Website: www.indofarm.in

