

















INDO FARM 3060 DI HT C-MESH 2WD/4WD

Technical Specifications

		2WD	4WD	
H.P. Category		50	4WD	
		4 Stroke, Naturally aspirated, DI, Diesel Engine		
No. of Cylinders		Four		
Bore/Stroke		105/118 mm		
Rated Speed		2000 RPM		
Max Torque		215 Nm		
Air Cleaner		Dry Type		
Fuel Pump		Inline. Make : Bosch India		
- пол пол р				
Cooling System		Water cooled		
Clutch System		Dual Clutch		
Hyd. Pump		Gear Type		
Lifting Capacity		1800 kg at Lower Link Ends		
Electrical		12 Volts-88 Ah-Battery Self Starter Motor & Alternator-42A		
Tyre	Front	7.50x16	9.50 x 24	
,,,,	Rear	16.9x28	16.9 x 28	
Wheel Track		1410-1490 mm	1515-1500 mm	
Dimensions	Length	3880 mm	3840 mm	
& [Width	1940 mm	1950 mm	
Weight	Height upto steering	1680 mm	1710 mm	
	Min. Ground Clearance	420 mm	380 mm	
	Wheel Base	2230 mm	2385 mm	
	Min. Turning Radius	4.25 m	4.5 m	
	Weight	2360 Kg	2640 kg	
P.T.O. 1. No. of Splines 2. PTO Speed		6 540 RPM		
Driver's Seat		Adjustable		
Transmission No. of Gear Speeds		8 Forward 2 Reverse		
Steering		Hydrostatic Power Steering		
Brake Type		Oil Immersed Brake		
Brake Actuation		Mechanical, independent right/left or combined		
Brake Actuati	ion	Mechanical, independe	ent right/left or combined	

Hydraulic (ADDC): Two lever, automatic Draft and Position control with mix control.

- 1. Position Control: To pre-select and automatically maintain certain position or depth of the implement attached to three-point-linkage.
- 2. Draft Control: To automatically raise and lower an attached implement as the draft or resistance of the implement increases or decreases.
- Mix Control: To automatically maintain shallow depths in loose soils where draft control is inefficient.

Gear Speed (16.9 x 28 Rear Tyre)							
		Road Speed (km/h)					
Direction	Gear	Low		High			
		Normal	16+4	Normal	16+4		
Forward	1	2.82	0.65	11.30	2.61		
	2	4.01	0.93	16.09	3.71		
	3	6.34	1.46	25.41	5.87		
	4	8.60	1.99	34.48	7.96		
Reverse	1	3.74	0.86	15.00	3.46		

Suitable Implements			
13 Tine Tiller			
3 Bottom M.B. Plough			
16 Disk Harrow			
6 Ton Trailor			
Rotavator 48 blades			

Accessories with Every Tractor

- Trailor Hook
- Draw bar
- Fender Guard
- Heavy Bumper
- Tool Kit
- Operator Manual

Accessories/Farm implements shown with tractors are not part of the standard model.

All the above specifications are subject to change without notice. For detailed information contact your nearest dealer.

Authorised Dealer

SPECIAL FEATURES



Powerful Engine

- 4-Cylinder, Fuel Efficient, heavy duty Engine.
- Engine volume of 4088 cc is best in class.
- More engine volume adds to life of engine



Neutral Safety Switch

- Tractor will not start in gear
- Adds to operator safety



Oil Immersed Disc Brakes

- Better braking operations
- . Long life due to oil cooling
- Lesser maintenance required



Best in class Maximum Engine Torque of 215 Nm



Power Steering (Std. feature):

- Easy steering operations.
- Increased level of operator comfort.



Big Fuel Tank of 63 ltrs.



Inline Fuel System :

- Low maintenance required.
- Easily available service centers.
- More acceptability in the market

High Max Speed: 35.0 Kmph 2WD/4WD

. It helps in haulage application.

. More haulage work in lesser time.

. More benefit transferred to farmers.



Digital instrument cluster,

· Easy to see at night.



Constant-Mesh Transmission with side shift gear shifting levers

- · Smooth gear shifting
- Add to operator comf



Newly designed Elegant bonnet & Graphics



Heavy duty front axle-

It has heavier front axle which adds to stability of the tractor in haulage application and reduces front lifting when carrying heavy loads.





AN ISO 9001: 2015 CERTIFIED COMPANY

Export Promotion Industrial Park, Phase-II, Baddi - 173205 Distt. Solan, H.P. Tel.: +91-1795-274242 to 247, Email: mail@indofarm.in, Website: www.indofarm.in