



















INDO FARM 3075 DI C-MESH TS-IV

Technical Specifications

H.P. Category		75	
Туре		Diesel, Four Stroke Direct Injection	
No. of Cylinders		Four	
Bore/Stroke		105/118 mm	
Rated Speed		2200 RPM	
Air Cleaner		Dry Type	
Fuel Pump		Inline, Make : Motorpal	
Cooling System		Water cooled	
Clutch System		Dual Clutch	
Hyd. Pump		Gear Type	
Lifting Capacity		2400 kg at Lower Link Ends	
Electrical		12 Volts-88 Ah-Battery	
		Self Starter Motor & Alternator	
Tyre	Front	7.50 x 16	
	Rear	16.9 x 30	
Wheel Track (Front-Rear)		1586-1480 mm	
Dimensions		3890 mm	
&	Width	1980 mm	
Weight	Height upto steering	1740 mm	
	Min. Ground Clearance	420 mm	
	Min. Turning Radius	4.5 m	
	Weight	2460 kgs	
P.T.O. 1. No. of Splines 2. PTO Speed		6 540 RPM	
Driver's Seat		Adjustable	
Transmission No. of Gear Speeds		8 Forward 2 Reverse	
Steering		Hydrostatic Power Steering	
Brake Type		Oil Immersed brake	
Brake Actuation		Mechanical, independent right/left or combined	
Parking Brake Actuation		Through hand lever, by locking brake pedals	

Hydraulic (ADDC) : Two lever, automatic Draft and Position control with mix control.

- 1. Position Control : To pre-select and automatically maintain certain position or depth of the implement attached to three-point-linkage.
- 2. Draft Control: To automatically raise and lower an attached implement as the draft or resistance of the implement increases or decreases.
- 3. Mix Control : To automatically maintain shallow depths in loose soils where draft control is inefficient.

Gear Speed (16.9 x 30 Rear Tyre)					
	Gear	Road Speed (km/h)			
Direction		Low	High		
Forward	1	2.92	11.72		
	2	4.16	16.69		
	3	6.58	26.36		
	4	8.92	35.76		
Reverse	1	3.88	15.55		

Suitable Implements
17/15 Tine Tiller
4 Bottom M.B. Plough
20 Disk Harrow
7.5 Ton Trailor
Rotavator 54 blades

Accessories with Every Tractor

- Trailor Hook
- Draw bar
- Fender Guard
- Front Weight
- Tool Kit
- Operator Manual
- · Canopy on Demand

Accessories/Farm implements shown with tractors are not part of the standard model.

All the above specifications are subject to change without notice. For detailed information contact your nearest dealer.

Authorised Dealer

SPECIAL FEATURES



Constant Mesh Gear Box with Side shift gear levers for easy gear shifting & more leg space.



Heavy 2400 kgs Lift, suitable for heavy implements and tipping trailers with higher loads



Straight Rear Axle, Less maintenance and repair



Heavy Duty Front Axle



Use to lift the trolley without lifting of hydraulic lift.



Oil immersed Brakes for better braking due to larger braking area & longer life due to oil cooling.



Aerodynamic Design- Easy approach for daily checkup like coolant level, air cleaner etc.



Dry Air Cleaner





AN ISO 9001 : 2015 CERTIFIED COMPANY

Export Promotion Industrial Park, Phase-II, Baddi - 173205 Distt. Solan, H.P. Tel.: +91-1795-274242 to 247, Email: mail@indofarm.in, Website: www.indofarm.in